



SECTION 1: Identification

Product identifier: U.N.X Freezer Cleaner

Other means of identification: Liquid specialty

SDS number: 588

Recommended use: Neutral cleaner

Recommended restrictions: Not for personal care

Manufacturer/Importer/Supplier/Distributor information

Company name: U.N.X. Incorporated
Address: 707 Arlington Blvd
Greenville, NC 27858
Telephone: Office hour (Mon-Fri)
8:00a.m. – 4:00p.m. (Eastern Time)
OFFICE NUMBER: 252-756-8616
Contact Person Jamie Singleton
E-mail: unx@unxinc.com
Emergency phone number: CHEMTEL (800) 255-3924 (24 HOURS)

SECTION 2: Hazard(s) identification

Classification of the substance or mixture:

Physical hazards

H225 Flammable liquid 2

Health hazards

Acute toxicity: Category 4
Skin corrosion/irritation: Category 2
Serious eye damage/eye irritation: Category 2

Label elements:



Signal word: Danger

Hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

SECTION 2: Hazard(s) identification (continue)**Precautionary statements****Prevention**

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P235 Keep cool.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fumes/ gas/ mist/ vapours/ spray.
 P264 Wash hands, arms, face and exposed skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this products.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / protective clothing/ eye protection/ face protection.

Response:

- P301+312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.
 P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.

Storage:

- P403+P235 Store in a well-ventilated place. Keep cool.

Disposal:

- P501 Dispose of contents/container in accordance with local/ regional/ national/ international Regulations.

Hazard(s) not otherwise Classified (HNOC) Not classified

SECTION 3: Composition/information on ingredients**Substance/Mixture**

Chemical name	CAS Number	Concentration (%)
Water	7732-18-5	40-60
Propane-1,2-diol	57-55-6	20-30
2-Propanol	67-63-0	15-25

SECTION 4: First-aid measures

Description of first aid measures

General advice: Remove victims from the danger zone without endangering your own safety.

Inhalation: Bring accident victims out into the fresh air. If patient has difficulty breathing, administer oxygen, keep the patient calm and warm. In case of unconsciousness place patient stably in side position for transportation. Call a physician immediately.

Skin contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before re-use. After contact with small amounts get medical attention if any discomfort or irritation continues. For large amounts, obtain medical attention.

Eye contact: Immediately flush eyes with gentle but large stream of water or eye wash solution for at least 15 minutes, lifting lower and upper eyelids occasionally. If possible remove any contact lenses and continue to wash. Call a physician, immediately.

Ingestion: If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. DO NOT induce vomiting, medical advice is required. Call a physician, immediately.

Most important symptoms/effects, acute and delayed:

Notes to physician: The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation: Irritation of nose, throat and airway.

Ingestion: May cause nausea and/or vomiting. Irritation of the mouth, throat, esophagus and gastrointestinal tract.

Skin contact/Skin irritation: Redness or rash may occur.

Eye contact: Causes irritation and burns to the eyes. Possible corneal damage.

Indication of immediate medical attention and special treatment needed, if necessary: Cases of eye contact and ingestion should be treated immediately. Have facilities in place to wash skin and eyes in case of exposure.

SECTION 5: Fire-fighting measures

Suitable extinguishing media: This product is not flammable under normal conditions. In case of fire use carbon dioxide (CO₂), foam, extinguishing powder. In cases of larger fires, water spray should be used. Use any means suitable for extinguishing surrounding fire. Water spray may be used to keep fire-exposed containers cool. If water is used, use in abundance to control heat.

Unsuitable extinguishing media: Do not use water jet as this can spread the fire. Do not use carbon dioxide in enclosed spaces with insufficient ventilation.

Specific hazards arising from the chemical: No unusual fire or explosion hazards noted. Product containers can melt in the heat of a fire. Packaging materials will be combustible and provide fuel for the fire. In the event of fire and/or explosion do not breathe fumes.

Special protective equipment and precautions for fire-fighters: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. During fire-fighting respirator with independent air-supply and airtight garment is required. Fight fire in early stages if safe to do so. Containers at risk of fire should be cooled with water and, if possible removed from the danger area. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate area of leak or spill. Ensure adequate ventilation/exhaust extraction. Put on protective equipment (see Section 8). Have emergency procedures in place for treating spillages, evacuating the area and informing the emergency services if necessary. Restrict access to the area until the spillage is treated, if large amounts of vapors are produced that will be hazardous to others, evacuate the area. When any other effects of spillages will affect the safety of others the area should be evacuated. Avoid ingestion, inhalation of vapors and contact with skin and eyes. Non-emergency personnel should be kept away from the area of spillage.

Environment precautions: Do not flush into surface water or sanitary sewers system. Avoid unauthorized discharge to the environment. Clean up any spillages immediately; prevent material from spreading and entering drains or sewage systems. Large spillages or uncontrolled discharge to water systems must be alerted to the Environmental Agency or other regulatory body. If spillages to land cannot be treated safely or if contamination will occur the Environment Agency must be alerted immediately. If the product has entered a foul drain or sewage system in significant amounts to cause a hazard then the local water treatment company must be informed.

Methods and materials for containment and cleaning up: Contain and recover liquid when possible. Small spillages should be absorbed with an inert, non-combustible absorbent. Large Spillages: Dam and absorb spillages with sand, earth or other inert material. Small Spillages: wipe up with absorbent material (e.g. cloth, fleece). Fit drain covers where they are available if the spillage is likely to enter the drainage system. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Ventilate area and allow drying before allowing access. Wash thoroughly after dealing with a spillage.

Reference to other sections: Refer to sections 8 and 13 for additional information.

SECTION 7: Handling and Storage

Precautions for safe handling: Keep in a tightly closed container and protect from physical damage. Store in a cool, dry and ventilated area. Keep away from sources of heat, moisture, incompatibilities, and direct sunlight. Avoid spilling the product. Do not wash out container and use it for other purposes. Avoid ingestion of the product, inhalation of any vapors/mists when produced and contact with skin and eyes. Do not eat, drink or smoke when handling. Wash at the end of each work shift, before eating, drinking, smoking and using the toilet. Do not mix with incompatible substances or mixtures. Remove contaminated clothing/footwear/equipment before entering eating areas or places that would expose others to the product. Do not use in areas close to drainage systems unless measures are in place to prevent access of product. Ensure emergency procedures are in place to treat spillages and cope with other situations such as evacuation. Provide eye washing and skin washing facilities, when handling large amounts a safety shower is recommended. Observe all warnings and precautions listed for the product.

Conditions for safe storage, including any incompatibilities: Store in closed original container at temperatures between 40°F and 80°F. If the product is transferred to another container, this should be made of a compatible material to the original container. Store away from heat, direct sunlight and moisture. Store in a stable situation to avoid spillages. It is advisable to store in a bunded area or use other protective measures such as a sump pallet or storage tray.

SECTION 8: Exposure control/personal protection**Control Parameters / Occupational exposure limits:****US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Chemical Name	CAS-No.	Value	ppm	mg/m ³
2-Propanol	67-63-0	PEL/TWA	400 ppm	980 mg/m ³
		STEL	500 ppm	1,225 mg/m ³

U.S. ACGIH Threshold Limit Values

Chemical Name	CAS-No.	Value	ppm	mg/L
2-Propanol	67-63-0	TWA	200 ppm	
		STEL	400 ppm	

USA. Workplace Environmental Exposure Levels (WEEL)

Chemical Name	CAS-No.	Value	Control parameters
Propane-1,2-diol	67-63-0	TWA	10.00 mg/m ³

Appropriate engineering controls:**Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the defined exposure limit requirements or guidelines. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition for details.

Individual protection measures, such as personal protective equipment (PPE)

Eye Protection: Use chemical safety goggles and / or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Hand protection: Wear protective gloves. Butyl rubber, rubber (natural, latex), nitrile, polyvinyl chloride (PVC). Be aware that latex gloves can produce an allergic reaction in sensitive individuals. Gloves should have a breakthrough time sufficient for the amount of handling but allow dexterity for safe movement and handling. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Gloves showing signs of degradation should be changed to avoid skin contamination. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. When removing used gloves apply proper technique by avoiding skin contact with the outer surface. When packages of the product are being handled during storage or transport it is advisable to wear protective gloves to prevent damage to the skin.

Personal Respirators (NIOSH Approved): If the exposure limit is exceeded, a full face piece respirator with high efficiency dust/mist filter may be worn up to 50 times the exposure limit. Wear suitable respiratory protection when vapors or mists are produced if the Workplace Exposure Limit is exceeded and there is insufficient ventilation or extraction. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. Respirator must be fitted with a cartridge suitable for the chemical of concern. Consult with the supplier as to the compatibility of the equipment with the chemical of concern. CAUTION: Air purifying respirators do not protect the user in oxygen deficient atmospheres, use air supplied system.

SECTION 8: Exposure control/personal protection

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: Wash hands, change out of clothes as soon as possible. Wash Clothes. Shower or bathe as soon as possible.

Other protective measures: Have an eye bath and safety shower close by.

SECTION 9: Physical and chemical properties

Appearance:	Liquid
Colour:	Orange liquid
Odour:	Alcohol odour
Odour Threshold:	No data available
pH:	7 ± 0.5
Melting point/range:	No data available
Boiling point/range:	No data available
Flash point:	No data available
Evaporation rate:	No data available
Flammability (solid, gas):	No data available
Upper/lower flammability of explosive limits:	No data available
Vapour pressure (mm Hg):	No data available
Vapour density (Air=1):	No data available
Relative density:	No data available
Solubility(ies):	Excellent
Partition coefficient (n-octanol/water):	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, dynamic:	25

Other Information: This product does not contain phosphates.

SECTION 10: Stability and reactivity

Reactivity and/or chemical stability: No specific reactivity hazards associated with this product. Product is very stable under normal conditions.

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to avoid: Avoid heat, direct sunlight, and moisture. Avoid storage with incompatible materials. Avoid storage in freezing conditions. Avoid storage near to unprotected drainage systems. It is advisable to store the product within some form of containment to prevent spillages reaching drainage systems. Avoid storage in an unstable manner or in a situation that would result in exposure to the product.

Incompatible materials: -Strong oxidizers

Hazardous decomposition products: Mild decomposition can result in evolution of hydrogen.

SECTION 11: Toxicological information

Acute toxicity: Toxicological testing has not been conducted with this material. The toxicology information listed below us based on the components of this material.

Category 4- Oral/Dermal/Inhalation: Harmful if; swallowed/in contact with skin/inhaled.

2-Propanol – ATE (Acute Toxicity Estimate)		
Oral LD ₅₀ > 2,000 mg/kg (Rat)	Dermal LD ₅₀ > 2,000 mg/kg (Rabbit)	Inhalation LC ₅₀ > 5,000 ppm, 1 hr (Rat)

Propane-1,2-diol – ATE (Acute Toxicity Estimate)	
Oral LD ₅₀ 20,000 - 34,000 mg/kg (Rat)	Dermal LD ₅₀ > 10,000 mg/kg (Rabbit)

Skin Corrosion/ irritation: May cause irritation of the skin. Not known to be corrosive.

Serious eye damage/irritation: May cause irritation and serious eye damage.

Respiratory or skin sensitization: Classification not possible.

Germ cell mutagenicity: Classification not possible.

Carcinogenicity: Classification not possible

Reproductive toxicity: Classification not possible.

Specific Target Organ Toxicity - Single Exposure: Classification not possible.

Specific Target Organ Toxicity - Repeated Exposure: Classification not possible. Isopropyl alcohol caused kidney effects in male rats although data is not considered relevant to humans.

Aspiration hazard: Classification not possible.

SECTION 12: Ecological information

Toxicity: Do not allow to escape into waterways, wastewater or soil. Ecotoxicological studies of the product are not available. Please find below the data available to us from raw materials:

Aquatic ecotoxicity:

2-Propanol			
Fish LC/EC/IC ₅₀ > 100 mg/L	Aquatic Invertebrates LC/EC/IC ₅₀ > 1,000 mg/L	Algae LC/EC/IC ₅₀ > 100 mg/L	Microorganism LC/EC/IC ₅₀ > 1,000 mg/L

SECTION 12: Ecological information (continued)

Propane-1,2-diol		
Acute LC ₅₀ (Water Flea) (Daphnia Magna) 4,850-34,400 mg/L	Acute LC ₅₀ : Rainbow trout (Oncorhynchus mykiss) About 44,000 mg/L	Acute LC ₅₀ : Fathead minnow (Pimephales Promelas) 46,500-54,900 mg/L

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential: No data available for this product.

Mobility in Soil: No data available for this product.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

General information

Do not allow unauthorized disposal to the environment. If operators are exposed to vapors during the disposal process then suitable respiratory protection should be worn. All other personal protective equipment as described in section 8 should be worn.

Disposal methods:

Avoid unauthorized disposal. Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with federal, state/provincial and local laws and regulations. For a small spill, immediately hose down with cool water and dispose to drain. For a large spill, dike, collect and contact local authorities about disposal.

SECTION 14: Transport information

UN Number:	NA 1993
UN Proper Shipping Name:	COMBUSTIBLE LIQUID, N.O.S., (2-PROPANOL)
Transport hazard class(es):	
DOT Hazard Class:	Not available
DOT Subsidiary Hazard Class:	Not available
Label:	COMBUSTIBLE
Packing group, if available:	III
Environmental Hazards:	Not available
Special precautions for user:	Not available

Transport in bulk according to Annex II of MARPOL 73/78³ and the IBC Code ³: Not applicable

SECTION 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Unless otherwise noted, no components are SARA TITLE 3 SECTION 313 40 CFR listed materials.

The ingredients of this product are listed on the TSCA inventory.

This product is not made with VOC'S that could cause damage to the ozone layer.

SARA 311/312 Tier II Hazard Ratings:

This mixture contains substances listed under the 311/312 hazard category: Fire Hazard, Acute Health Hazard, and Chronic Health Hazard.

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS #	CA	FL	MA	MN	NJ	PA
2-Propanol	67-63-0	No	No	Yes	No	Yes	Yes
Propane-1,2-diol	57-55-6	No	No	No	No	Yes	Yes

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information including date of preparation or last revision

Chemical State: Liquid

Chemical Type: Mixture

Issue Date: 04-22-2015

Revision Date: -

Version #: 01

1	Health
2	Flammability
0	Physical Hazards
C	Personal Protection

To the best of our knowledge, the information contained herein is accurate. **However, neither U.N.X. Incorporated nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.** Final determination of suitability of any material is the sole responsibility of the user. All materials may represent unknown hazards and should be used within caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.